

# Py-Sect Insecticide

## Ensign Laboratories

Chemwatch: 23-4003

Version No: 2.1.1.1

Material Safety Data Sheet according to NOHSC and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: 01/01/2013

Print Date: 16/03/2015

Initial Date: Not Available

S.Local.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

Product name	Py-Sect Insecticide
Synonyms	PY-SECT INSECTICIDE
Proper shipping name	AEROSOLS
Other means of identification	Not Available

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Application is by spray atomisation from a hand held aerosol pack Insecticide spray.
--------------------------	---

### Details of the manufacturer/importer

Registered company name	Ensign Laboratories
Address	490 Wellington Rd Mulgrave 3170 VIC Australia
Telephone	+61 3 9550 1500
Fax	+61 3 9560 5545
Website	Not Available
Email	Not Available

### Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	+61 3 9573 3112
Other emergency telephone numbers	Not Available

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

**HAZARDOUS SUBSTANCE. DANGEROUS GOODS.** According to the Criteria of NOHSC, and the ADG Code.

#### CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	4	
Toxicity	0	
Body Contact	2	
Reactivity	1	
Chronic	2	

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

Poisons Schedule	Not Applicable
Risk Phrases [1]	<b>R50/53</b> Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. <b>R44</b> Risk of explosion if heated under confinement. <b>R36</b> Irritating to eyes. <b>R67</b> Vapours may cause drowsiness and dizziness. <b>R12</b> Extremely flammable.
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI



Relevant risk statements are found in section 2

Indication(s) of danger	F+, Xi, N
-------------------------	-----------

#### SAFETY ADVICE

Continued...

## Py-Sect Insecticide

S09	Keep container in a well ventilated place.
S15	Keep away from heat.
S16	Keep away from sources of ignition. No smoking.
S23	Do not breathe gas/fumes/vapour/spray.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
S29	Do not empty into drains.
S33	Take precautionary measures against static discharges.
S35	This material and its container must be disposed of in a safe way.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.
S39	Wear eye/face protection.
S40	To clean the floor and all objects contaminated by this material, use water and detergent.
S41	In case of fire and/or explosion, DO NOT BREATHE FUMES.
S43	In case of fire use...
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well ventilated areas.
S56	Dispose of this material and its container at hazardous or special waste collection point.
S57	Use appropriate container to avoid environmental contamination.
S61	Avoid release to the environment. Refer to special instructions/Safety data sheets.
S64	If swallowed, rinse mouth with water (only if the person is conscious).

## Other hazards

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

## Substances

See section below for composition of Mixtures

## Mixtures

CAS No	%[weight]	Name
64-17-5	30-60	<a href="#">ethanol</a>
51-03-6	1-10	<a href="#">piperonyl butoxide</a>
8003-34-7	1-10	<a href="#">pyrethrum</a>
68476-85-7.	30-60	<a href="#">hydrocarbon propellant</a>
		NOTE: Manufacturer has supplied full ingredient information to allow CHEMWATCH assessment.

NOTE: Manufacturer has supplied full ingredient information to allow CHEMWATCH assessment.

## SECTION 4 FIRST AID MEASURES

## Description of first aid measures

Eye Contact	<p>If aerosols come in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<p>If solids or aerosol mists are deposited upon the skin:</p> <ul style="list-style-type: none"> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Remove any adhering solids with industrial skin cleansing cream.</li> <li>▶ <b>DO NOT use solvents.</b></li> <li>▶ Seek medical attention in the event of irritation.</li> </ul>
Inhalation	<p>If aerosols, fumes or combustion products are inhaled:</p> <ul style="list-style-type: none"> <li>▶ Remove to fresh air.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>
Ingestion	<p>Not considered a normal route of entry.</p> <ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> </ul>

## Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For chronic or short term repeated exposures to pyrethrum and synthetic pyrethroids:

- ▶ Mammalian toxicity of pyrethrum and synthetic pyrethroids is low, in part because of poor bioavailability and a large first pass extraction by the liver.
- ▶ The most common adverse reaction results from the potent sensitising effects of pyrethrins.
- ▶ Clinical manifestations of exposure include contact dermatitis (erythema, vesiculation, bullae); anaphylactoid reactions (pallor, tachycardia, diaphoresis) and asthma. [*Ellenhor Barceloux*]
- ▶ In cases of skin contact, it has been reported that topical application of Vitamin E Acetate (alpha-tocopherol acetate) has been found to have high therapeutic value, eliminating almost all skin pain associated with exposure to synthetic pyrethroids. [*Incitec*]

## SECTION 5 FIREFIGHTING MEASURES

### Extinguishing media

#### SMALL FIRE:

- ▶ Water spray, dry chemical or CO<sub>2</sub>

#### LARGE FIRE:

- ▶ Water spray or fog.

### Special hazards arising from the substrate or mixture

#### Fire Incompatibility

- ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

### Advice for firefighters

#### Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- ▶ May be violently or explosively reactive.
- ▶ Wear breathing apparatus plus protective gloves.
- ▶ Prevent, by any means available, spillage from entering drains or water course.
- ▶ If safe, switch off electrical equipment until vapour fire hazard removed.
- ▶ Use water delivered as a fine spray to control fire and cool adjacent area.
- ▶ **DO NOT** approach containers suspected to be hot.
- ▶ Cool fire exposed containers with water spray from a protected location.
- ▶ If safe to do so, remove containers from path of fire.
- ▶ Equipment should be thoroughly decontaminated after use.

#### Fire/Explosion Hazard

- ▶ Liquid and vapour are highly flammable.
  - ▶ Severe fire hazard when exposed to heat or flame.
  - ▶ Vapour forms an explosive mixture with air.
  - ▶ Severe explosion hazard, in the form of vapour, when exposed to flame or spark.
  - ▶ Vapour may travel a considerable distance to source of ignition.
  - ▶ Heating may cause expansion or decomposition with violent container rupture.
  - ▶ Aerosol cans may explode on exposure to naked flames.
  - ▶ Rupturing containers may rocket and scatter burning materials.
  - ▶ Hazards may not be restricted to pressure effects.
  - ▶ May emit acrid, poisonous or corrosive fumes.
  - ▶ On combustion, may emit toxic fumes of carbon monoxide (CO).
- Combustion products include; carbon dioxide (CO<sub>2</sub>) other pyrolysis products typical of burning organic material **Contains low boiling substance:** Closed containers may rupture due to pressure buildup under fire conditions.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

#### Minor Spills

- Environmental hazard - contain spillage.
- ▶ Clean up all spills immediately.
  - ▶ Avoid breathing vapours and contact with skin and eyes.
  - ▶ Wear protective clothing, impervious gloves and safety glasses.
  - ▶ Shut off all possible sources of ignition and increase ventilation.
  - ▶ Wipe up.
  - ▶ If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.
  - ▶ Undamaged cans should be gathered and stowed safely.

#### Major Spills

- Environmental hazard - contain spillage.
- ▶ Clear area of personnel and move upwind.
  - ▶ Alert Fire Brigade and tell them location and nature of hazard.
  - ▶ May be violently or explosively reactive.
  - ▶ Wear breathing apparatus plus protective gloves.
  - ▶ Prevent, by any means available, spillage from entering drains or water courses
  - ▶ No smoking, naked lights or ignition sources.
  - ▶ Increase ventilation.
  - ▶ Stop leak if safe to do so.
  - ▶ Water spray or fog may be used to disperse / absorb vapour.
  - ▶ Absorb or cover spill with sand, earth, inert materials or vermiculite.
  - ▶ If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated.
  - ▶ Undamaged cans should be gathered and stowed safely.
  - ▶ Collect residues and seal in labelled drums for disposal.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

#### Safe handling

- ▶ Avoid all personal contact, including inhalation.
- ▶ Wear protective clothing when risk of exposure occurs.
- ▶ Use in a well-ventilated area.

## Py-Sect Insecticide

	<ul style="list-style-type: none"> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ Avoid smoking, naked lights or ignition sources.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ <b>DO NOT incinerate or puncture aerosol cans.</b></li> <li>▶ <b>DO NOT spray directly on humans, exposed food or food utensils.</b></li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this MSDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can</li> <li>▶ Store in original containers in approved flammable liquid storage area.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ Keep containers securely sealed. Contents under pressure.</li> <li>▶ Store away from incompatible materials.</li> <li>▶ Store in a cool, dry, well ventilated area.</li> <li>▶ Avoid storage at temperatures higher than 40 deg C.</li> <li>▶ Store in an upright position.</li> <li>▶ Protect containers against physical damage.</li> <li>▶ Check regularly for spills and leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this MSDS.</li> </ul>

### Conditions for safe storage, including any incompatibilities

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Aerosol dispenser.</li> <li>▶ Check that containers are clearly labelled.</li> </ul>
<b>Storage incompatibility</b>	<p>Pyrethrins and permethrins:</p> <ul style="list-style-type: none"> <li>▶ are unstable in the presence of light, heat, moisture and air</li> <li>▶ are hydrolysed by oxygen and/ or sunlight</li> <li>▶ may react with strong oxidisers to produce fire and explosions</li> <li>▶ are incompatible with alkalis</li> <li>▶ Avoid strong bases.</li> </ul>

### PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	ethanol	Ethyl alcohol	1880 mg/m <sup>3</sup> / 1000 ppm	Not Available	Not Available	Not Available
Australia Exposure Standards	pyrethrum	Pyrethrum	5 mg/m <sup>3</sup>	Not Available	Not Available	Sen
Australia Exposure Standards	hydrocarbon propellant	LPG (liquified petroleum gas)	1800 mg/m <sup>3</sup> / 1000 ppm	Not Available	Not Available	Not Available

#### EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ethanol	Ethyl alcohol; (Ethanol)	Not Available	Not Available	Not Available
piperonyl butoxide	Piperonyl butoxide	1.2 mg/m <sup>3</sup>	13 mg/m <sup>3</sup>	1200 mg/m <sup>3</sup>
hydrocarbon propellant	Liquified petroleum gas; (L.P.G.)	3,000 ppm	3200 ppm	19000 ppm

Ingredient	Original IDLH	Revised IDLH
ethanol	15,000 ppm	3,300 [LEL] ppm
piperonyl butoxide	Not Available	Not Available
pyrethrum	5,000 mg/m <sup>3</sup>	5,000 [Unch] mg/m <sup>3</sup>
hydrocarbon propellant	19,000 [LEL] ppm	2,000 [LEL] ppm

### Exposure controls

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection.</p> <p>Provide adequate ventilation in warehouse or closed storage areas.</p>
---	---

Continued...

## Py-Sect Insecticide

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Speed:
aerosols, (released at low velocity into zone of active generation)	0.5-1 m/s
direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

## Personal protection



## Eye and face protection

- ▶ Safety glasses with side shields.
- ▶ Chemical goggles.
- ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

## Skin protection

See Hand protection below

## Hands/feet protection

- ▶ No special equipment needed when handling small quantities.
- ▶ **OTHERWISE:**
- ▶ For potentially moderate exposures:
- ▶ Wear general protective gloves, eg. light weight rubber gloves.
- ▶ For potentially heavy exposures:
- ▶ Wear chemical protective gloves, eg. PVC. and safety footwear.

## Body protection

See Other protection below

## Other protection

No special equipment needed when handling small quantities.

- OTHERWISE:**
- ▶ Overalls.
  - ▶ Skin cleansing cream.
  - ▶ Eyewash unit.
  - ▶ Do not spray on hot surfaces.

## Thermal hazards

Not Available

## Recommended material(s)

## GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index".**

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Py-Sect Insecticide

Material	CPI
BUTYL	A
NEOPRENE	A
NITRILE	A
NITRILE+PVC	A
PE/EVAL/PE	A
PVC	B
NATURAL RUBBER	C
NATURAL+NEOPRENE	C

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise

## Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	AX-AUS / Class1 P2	-
up to 50	1000	-	AX-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	AX-2 P2
up to 100	10000	-	AX-3 P2
100+			Airline**

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## Py-Sect Insecticide

be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

<b>Appearance</b>	Supplied as an aerosol pack. Contents under <b>PRESSURE</b> . Contains highly flammable hydrocarbon propellant.		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	Not Available
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Available	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	Not Available	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	Not Available	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Available	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Available	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	Not Available	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	Not Available	<b>Gas group</b>	Not Available
<b>Solubility in water (g/L)</b>	Immiscible	<b>pH as a solution</b>	Not Available
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available

## SECTION 10 STABILITY AND REACTIVITY

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Elevated temperatures.</li> <li>▶ Presence of open flame.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

<b>Inhaled</b>	Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. <b>WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.</b>
<b>Ingestion</b>	Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments Ingestion may result in nausea, abdominal irritation, pain and vomiting
<b>Skin Contact</b>	Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. Spray mist may produce discomfort Open cuts, abraded or irritated skin should not be exposed to this material
<b>Eye</b>	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
<b>Chronic</b>	Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapours especially at higher temperatures. As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice. <b>WARNING: Aerosol containers may present pressure related hazards.</b>

<b>Py-Sect Insecticide</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
<b>ethanol</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 17100 mg/kg <sup>[1]</sup>	Eye (rabbit): 500 mg SEVERE
	Inhalation (rat) LC50: 64000 ppm/4h <sup>[2]</sup>	Eye (rabbit): 100mg/24hr-moderate
	Oral (rat) LD50: >11872769 mg/kg <sup>[1]</sup>	Skin (rabbit): 20 mg/24hr-moderate

## Py-Sect Insecticide

Skin (rabbit):400 mg (open)-mild

	TOXICITY	IRRITATION
piperonyl butoxide	dermal (rat) LD50: >7950 mg/kg <sup>[2]</sup>	Not Available
	Inhalation (rat) LC50: >5.9 mg/l4 h <sup>[1]</sup>	
	Oral (rat) LD50: 5630 mg/kg <sup>[1]</sup>	
pyrethrum	dermal (rat) LD50: 1350 mg/kg <sup>[2]</sup>	Not Available
	Oral (rat) LD50: 200 mg/kgd <sup>[2]</sup>	
hydrocarbon propellant	Inhalation (mouse) LC50: >15.6<17.9 mm/2 h <sup>[1]</sup>	Not Available
	Inhalation (mouse) LC50: 410000 ppm2 h <sup>[1]</sup>	
	Inhalation (rat) LC50: >570000<17.9 ppm15 min <sup>[1]</sup>	
	Inhalation (rat) LC50: >800000 ppm15 min <sup>[1]</sup>	
	Inhalation (rat) LC50: 1354.944 mg/L15 min <sup>[1]</sup>	
	Inhalation (rat) LC50: 1355 mg/l15 min <sup>[1]</sup>	
	Inhalation (rat) LC50: 1442.738 mg/L15 min <sup>[1]</sup>	
	Inhalation (rat) LC50: 1443 mg/l15 min <sup>[1]</sup>	
<b>Legend:</b>	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's msds Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

<b>ETHANOL</b>	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
<b>PIPERONYL BUTOXIDE</b>	The substance is classified by IARC as Group 3: <b>NOT</b> classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. Dermal (rabbit) LD50: >1880 mg/kg [Handbook of Toxicology] *Published value - probably not peer-reviewed ADI: 0.03 mg/kg
<b>PYRETHRUM</b>	Pyrethrins have low to moderate acute toxicity when swallowed, inhaled and on skin contact. They have a moderate irritant effect on the eye and skin (but do not sensitise the skin). The toxic effects of pyrethrin include tremors, laboured breathing, hyperactivity, thyroid disturbances, and liver effects. Animal testing has found that pyrethrins can cause tremors and convulsions before death and that pyrethrins are toxic to the axon. In testing involving animals, pyrethrins have been found to cause reproductive toxicity at sufficient doses, as well as benign liver tumours. There is not enough information to assess whether pyrethrins cause cancer in humans. There is evidence that pyrethrins are associated with disturbance of thyroid function. Pyrethroids are thought to have similar effects to pyrethrins.  ADI: 0.04 mg/kg/day
<b>HYDROCARBON PROPELLANT</b>	No significant acute toxicological data identified in literature search. inhalation of the gas

<b>Acute Toxicity</b>		<b>Carcinogenicity</b>	
<b>Skin Irritation/Corrosion</b>		<b>Reproductivity</b>	
<b>Serious Eye Damage/Irritation</b>		<b>STOT - Single Exposure</b>	
<b>Respiratory or Skin sensitisation</b>		<b>STOT - Repeated Exposure</b>	
<b>Mutagenicity</b>		<b>Aspiration Hazard</b>	

**Legend:** – Data required to make classification available  
 – Data available but does not fill the criteria for classification  
 – Data Not Available to make classification

**CMR STATUS**

Not Applicable

**SECTION 12 ECOLOGICAL INFORMATION****Toxicity**

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**DO NOT discharge into sewer or waterways.**

Continued...

**Persistence and degradability**

Ingredient	Persistence: Water/Soil	Persistence: Air
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
piperonyl butoxide	HIGH	HIGH

**Bioaccumulative potential**

Ingredient	Bioaccumulation
ethanol	LOW (LogKOW = -0.31)
piperonyl butoxide	HIGH (LogKOW = 4.75)



**Mobility in soil**

Ingredient	Mobility
ethanol	HIGH (KOC = 1)
piperonyl butoxide	LOW (KOC = 69.74)

**SECTION 13 DISPOSAL CONSIDERATIONS****Waste treatment methods**

Product / Packaging disposal	<ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> allow wash water from cleaning or process equipment to enter drains.</li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Consult State Land Waste Management Authority for disposal.</li> <li>▶ Discharge contents of damaged aerosol cans at an approved site.</li> <li>▶ Allow small quantities to evaporate.</li> <li>▶ <b>DO NOT</b> incinerate or puncture aerosol cans.</li> <li>▶ Bury residues and emptied aerosol cans at an approved site.</li> </ul>
------------------------------	---

**SECTION 14 TRANSPORT INFORMATION****Labels Required**

	
Marine Pollutant	
HAZCHEM	2YE

**Land transport (ADG)**

UN number	1950
Packing group	Not Applicable
UN proper shipping name	AEROSOLS
Environmental hazard	No relevant data
Transport hazard class(es)	Class : 2.1 Subrisk : Not Applicable
Special precautions for user	Special provisions : 63 190 277 327 344 Limited quantity : See SP 277

**Air transport (ICAO-IATA / DGR)**

UN number	1950
Packing group	Not Applicable
UN proper shipping name	Aerosols, flammable
Environmental hazard	No relevant data
Transport hazard class(es)	ICAO/IATA Class : 2.1 ICAO / IATA Subrisk : Not Applicable ERG Code : 10L



<b>Special precautions for user</b>	Special provisions	A145A167A802
	Cargo Only Packing Instructions	203
	Cargo Only Maximum Qty / Pack	150 kg
	Passenger and Cargo Packing Instructions	203
	Passenger and Cargo Maximum Qty / Pack	75 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Y203
	Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

**Sea transport (IMDG-Code / GGVSee)**

<b>UN number</b>	1950	
<b>Packing group</b>	Not Applicable	
<b>UN proper shipping name</b>	AEROSOLS	
<b>Environmental hazard</b>	Not Applicable	
<b>Transport hazard class(es)</b>	IMDG Class	2.1
	IMDG Subrisk	See SP63
<b>Special precautions for user</b>	EMS Number	F-D , S-U
	Special provisions	63 190 277 327 344 959
	Limited Quantities	See SP277

**SECTION 15 REGULATORY INFORMATION****Safety, health and environmental regulations / legislation specific for the substance or mixture**

<b>ethanol(64-17-5) is found on the following regulatory lists</b>	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"
<b>piperonyl butoxide(51-03-6) is found on the following regulatory lists</b>	"Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Hazardous Substances Information System - Consolidated Lists"
<b>pyrethrum(8003-34-7) is found on the following regulatory lists</b>	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Hazardous Substances Information System - Consolidated Lists"
<b>hydrocarbon propellant(68476-85-7.) is found on the following regulatory lists</b>	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"

**SECTION 16 OTHER INFORMATION****Other information****Ingredients with multiple cas numbers**

Name	CAS No
hydrocarbon propellant	68476-85-7., 68476-86-8.

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references)

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.